

## SHAFT SPECIFICATIONS




### F16 COMBO IRON

MODEL	AVAILABILITY	FLEX	WEIGHT	LENGTH	TIP	BUTT	TORQUE
R/S IRON	●	R/S	118g	40"	.370"	.600"	2.0°



### MODUS 3 (120)

MODEL	AVAILABILITY	FLEX	WEIGHT	LENGTH	TIP	BUTT	TORQUE
S-IRON	●	S	114g	37-41"	.355"	.600"	1.9-1.6°
X-IRON	●	X	120g	37-41"	.355"	.600"	1.7-1.4°
TX-IRON	●	TX	126g	37-41"	.355"	.600"	1.6-1.4°



### MODUS TOUR 130

MODEL	AVAILABILITY	FLEX	WEIGHT	LENGTH	TIP	BUTT	TORQUE
R-IRON	●	R	121g	37-41"	.370"	.600"	1.8-1.3°
S-IRON	●	S	124g	37-41"	.370"	.600"	1.7-1.2°
X-IRON	●	X	129g	37-41"	.370"	.600"	1.6-1.2°
R TAPER IRON	●	R	121g	37-41"	.355"	.600"	-
S TAPER IRON	●	S	124g	37-41"	.355"	.600"	-
X TAPER IRON	●	X	129g	37-41"	.355"	.600"	-

● = STOCK ● = SPECIAL ORDER



## NEW MODUS WEDGE

MODEL	AVAILABILITY	FLEX	WEIGHT	LENGTH	TIP	BUTT	TORQUE
105 WEDGE	●	R/S	111g	37"	.355"	.600"	1.6°
115 WEDGE	●	R/S	122g	37"	.355"	.600"	1.5°
125 WEDGE	●	R/S	133g	37"	.355"	.600"	1.3°



## NS PRO 850, 950, 1050, 1150

MODEL	AVAILABILITY	FLEX	WEIGHT	LENGTH	TIP	BUTT	TORQUE
850 R IRON	●	R	87g	35-39.5"	.370"	.600"	2.1°
850 S IRON	●	S	91g	35-39.5"	.370"	.600"	1.9°
850 R TAPER IRON	●	R	87g	35-39.5"	.355"	.600"	2.1°
850 S TAPER IRON	●	S	91g	35-39.5"	.355"	.600"	1.9°
950 R IRON	●	R	94.5g	35-39.5"	.370"	.610"	2.0°
950 S IRON	●	S	98g	35-39.5"	.370"	.610"	1.9°
950 R TAPER IRON	●	R	94.5g	35-39.5"	.355"	.610"	2.0°
950 S TAPER IRON	●	S	98g	35-39.5"	.355"	.610"	1.9°
1050 R IRON	●	R	106g	35-39"	.370"	.600"	2.0°
1050 S IRON	●	S	109.5g	35-39"	.370"	.600"	1.8°
1050 R TAPER IRON	●	R	106g	35-39"	.355"	.600"	2.0°
1050 S TAPER IRON	●	S	109.5g	35-39"	.355"	.600"	1.8°
1150 R IRON	●	R	111.5g	35-39"	.370"	.600"	1.9-1.6°
1150 S IRON	●	S	116g	35-39"	.370"	.600"	1.8-1.4°
1150 X IRON	●	X	121.5g	35-39"	.370"	.600"	1.6-1.3°
1150 R TAPER IRON	●	R	111.5g	35-39"	.355"	.600"	1.9-1.6°
1150 S TAPER IRON	●	S <sup>3</sup>	116g	35-39"	.355"	.600"	1.8-1.4°
1150 X TAPER IRON	●	X	121.5g	35-39"	.355"	.600"	1.6-1.3°

● = STOCK ● = SPECIAL ORDER



## NS PRO REGIO FORMULA GRAPHITE

MODEL	AVAILABILITY	FLEX	WEIGHT	LENGTH	TIP	BUTT	TORQUE
55-R2 WOOD	●	R2	52.5g	46"	.335"	.600"	3.9°
55-R WOOD	●	R	55.5g	46"	.335"	.605"	3.8°
55-S WOOD	●	S	58g	46"	.335"	.608"	3.8°
65-R WOOD	●	R	63g	46"	.335"	.605"	2.9°
65-S WOOD	●	S	66g	46"	.335"	.608"	2.9°
65-X WOOD	●	X	68.5g	46"	.335"	.610"	2.9°
75-R WOOD	●	R	75.5g	46"	.335"	.608"	2.5°
75-X WOOD	●	X	78.5g	46"	.335"	.610"	2.5°



## NS PRO ZELOS 7

MODEL	AVAILABILITY	FLEX	WEIGHT	LENGTH	TIP	BUTT	TORQUE
R IRON	●	R	74g	38.5-35"	.355"	.570"	2.8°
S IRON	●	S	77.5g	38.5-35"	.355"	.570"	2.6°

● = STOCK ● = SPECIAL ORDER